| 21ST CENTURY - STANDARD WINDOW ORDER | | | Please Read Attached Specification Guide SG1312 Before Placing Order | | | | Page | of |
|--|----------------------------|-----------------------------|---|----------------------------|---------------------------|---|-------------------------------|--|
| Customer | | | Goods | £ | | Order Date | | |
| Address | | | | [| | Customer Signat | ure | (By Signing this order |
| | | | VAT | £ | | | | you agree to Affordable Window Systems Ltd. |
| | | | Total | £ | | | | Terms & Conditions) |
| Tel No | | | | | L. | | | |
| Post Code Job Reference | | | | | | Date Req. Also invoice date) | | |
| _ | | | PRODUCTION | | | | DELIVERY | CODE |
| | Quote Date | | | | | | | |
| KOMMERLING | | D Colours Both | | Profile Code | | CODE Co | lour Outsid | |
| A57 Cert 3504 STD | A60 Cert 4319 STD [] Wr | hite | [] | K=Kommerling A=Aluplast | g (15 Day Lead Tin | ^{ie)} K/A/S Cr | eam on Whit | e [] |
| 67mm | A60 Cert 4504 A+12 [] Oa | ak | [] | S=Swish | | | ey on White | [] |
| Slim Sash | 75mm [] Ro | osewood | <u>[]</u> | | our both Sides | | ack on White | [] |
| Trickle Vent to Head only Large Head will be Used | Bead Black STD Grey [] ST | D Colour or | n White | K/A/SAntiqı K/APolar | | | tq pine on W plar on White | L J |
| Bead Black Gasket Std | SWISH Oa | ak on White | [] | KBlack | | | green On W | L J |
| Bead White Gasket | A60mm Cert 3505 STD[] Ro | osewood On | White [] | KCrear | | | 0 | hite Light Green |
| | | | | Base Colour will | be white unless a r | nore suitable colour i | | |
| View | Item Qty Location | Cill | Add- | On S, M, L | Clear T | oughened | E | xtras |
| Inside |] | None 85mm | Lon | | Pattern | | Coupler Q | ty Length |
| Outside | Width Height | 150mr | 1 1 | | Overlay | | 3mm "I" 8mm Reinf | |
| Glass 28mm STD | | 180mr | <u> </u> | | ecoration | | Baypole Q | ty Length |
| | Transom Drop | Welde Draina | L J | | Silver | Georgian | Variable | |
| Size Only No Glass | | Conce | eal | | Aged Diamond | 18mm 25mm | 135° Pole 90° Post | |
| If <u>A RATED</u> is ticked then We Need Your BFRC No | | Face | L] —— le Vent ^{Hinge} | es | Diamond] Square | White | Bay Jacks | n/a on Komm |
| We need Tour <u>BFRC NO</u> | Mullion Split | Head | [] Easy C | Clean Fire | 6mm [] | • WGrain | Deductions ma | de for couplers |
| | / | Sash# | # [] | | 9mm | Astragal | | lotes |
| | Item Qty Location | Cill | (Add- | On S, M, L | Clear | oughened | | _ |
| | | None | | | Pattern | | | Cills |
| Warm Edge A Rated | Width Height | 85mm 150mr | 5 4 | | Overlay | | | and |
| Black Std | | 180mr | <u> </u> | D/ | ecoration | | | ons a |
| White Spacer Bar NON A RATED | Transom Drop | Welde Draina | L J | | Silver | Georgian | | dd -bb |
| Silver [] | ıl l | Conce | eal | | Aged [] | 18mm 25mm | | A Br |
| Bronze | | Face | L] —— le Vent ^{Hinge} | es 2 | Square | White | | ludi |
| Gold | Mullion Split | Head | Easy C | Clean Fire | 6mm [] 9mm [] | U WGrain | | Exc |
| Window Handles | / | Sash# | # [] 1000 | | 311111 | Astragai | | are |
| White | Item Qty Location | Cill | Add- | On S, M, L | Clear | oughened | | Sizes |
| Gold Bright | | None 85mm | L Left | | Pattern | | | ail S |
| Silver Bright [] Satin [] | Width Height | 150mr | 2 4 | | Overlay | | | Midr |
| Door Type | Transom Drop | 180mr Welde | 5 d _ | De | ecoration | | | and |
| Single | | Draina | age | | Silver | Georgian | | ion |
| Tilt & Slide Patio | il | Conce Face | eal [] Bottor | | Aged Diamond | 18mm 25mm | | Mul |
| In-Line Patio | Mullian Onlike | | le Vent Hinge | s r r r - | Diamond Square | 18mm 25mm 00 White | | , mo |
| Composite | Mullion Split | Head | Restri | ictor | 6mm | WGrain Astragal | | rans |
| Door Opening | <i>//</i> | Sash# | ≠ L] | | 0[] | , ionagai[] | | L) s |
| Open In | Item Qty Location | Cill | | On S, M, L | Clear | Foughened | | l Cill |
| Open Out | | None 85mm | | | Pattern | | | anc |
| Door Handle Type | Frame Width Frame Height | t 150m | | | Overlay | | | Ons |
| Lever/Lever Std | Door Width | 180m Welde | | | | | | Add |
| High Security | | Drain | nage | | ecoration Silver | Georgian | | qe |
| Door Handle Colour | Transom Drop | Conce Face | 노크 | | Aged | 18mm | Profile * Depending or | |
| White | Midrail Height | | le Vent | gs | Square | 25mm [] 000 White [] 00 WGrain [] | | dered it will be ຼູ wish until stock ຜູ |
| Gold Satin | | Head | I [] ^{Sml L} | ion Head | 6mm[] | Write WGrain | is used up. | 4504 +12 has |
| Silver Satin | Restricted Opening | Sash | Scrol | L J | 9mm [] | Astragal | a 40mm Trip | le Glazed |
| Black | | / | Urn Urn & | Viewer Pa | inel | | Unit. The Be only Availat | ad gasket is 🏻 🖇 ble in Black 🔅 Ö |
| Gold Polished** | Threshold Master | Letterbox Plac | trail | · · · · · | | | SALES PERS | |
| Chrome Bright** | Large | Side P | | Numerals Pa | anel Overlay | | | |
| ** Not High Security | | Panel [] Door Restrictor | r | | | | FEB 2014 | |

SPECIFICATION GUIDE NUMBER SG1312

MISSING INFORMATION - DEFAULT SPECIFICATION

Where information is missing for some items we will assume these items will be made to match other windows/doors on the order.

Where information has not been provided on the order form, windows/doors will be **viewed from the** outside and have silver/chrome handles/furniture, concealed drainage with 150mm cill, black warm edge spacer bar, clear glass, 400mm transom drop and mullions will be split equally if the window is less than 1450mm wide. Wider windows will have a mullion split of 650mm if an opening sash is specified. Mid-rail height will be 840mm excluding cill, doors will have small PVCU frame threshold.

If the trickle vent is not drawn on the window diagram, the production department will decide the position. If the trickle vent position is drawn but the trickle vent head/sash box is not ticked, a trickle vent will be fitted as per the drawing. Windows with a Slim Sash can only have the vent in the head with a concealed drip hood.

Windows/doors made using the above default specification because of missing information will be charged for even if the window/door is rejected by the customer.

If you specify a casement sash or entrance door/French door larger than the dimensions given below we will manufacture but will not guarantee the performance of the oversized item.

SIZE RESTRICTION FOR CASEMENT WINDOWS

The minimum size is 300mm x 300mm. Opening sash windows can be made to a maximum of 700mm width x 1300mm high for a side hung. For top hung sashes the maximum width is 1400mm but the height plus width cannot exceed 2100mm (i.e. 1400mm + 700mm or 1300mm + 800mm etc.)

If restrictors are used the maximum size is 1200mm by 1200mm but not exceeding 1200mm in height or width if the 2100mm size restriction has been exceeded.

TILT & TURN SIZE RESTRICTION

The minimum width is 400mm and height is 350mm the maximum width is 1440mm and height is 2440mm. Please check before ordering if the size exceeds 2.4m². Note: The width cannot be more than one and a half times the height.

SIZE RESTRICTION FOR ENTRANCE/FRENCH DOORS

The maximum width of an entrance door including outer frame is 1084mm and for French doors is 2118mm including outerframe, maximum height 2234mm.

The maximum height without guarantee is 2384mm. The maximum side panel is 1500mm and the minimum is 428mm to accomodate a letterbox. A Door handle will only be fitted to the master door if the slave door is narrower than the master door.

DOOR PANEL SIZE RESTRICTIONS

Any door less than 840mm wide will not accomodate many of the infill panels.

The Bristol panel requires a door width of 894mm & the Oxford panel 874mm - please check availability for narrow doors.

'A' RATING

Only windows with 57mm Kommerling/60mm Aluplast/Swish with a warm edge spacer are 'A' Rated. A BFRC number is required for unglazed windows. The following products cannot be 'A' Rated: windows with 6mm glass, large outer frame, Aluminium spacer bar, Tilt & Turn windows, Entrance/French doors. Casement windows with a floating mullion (French window).

Where 'A' Rating has been specified on the order form and any of the above specification is required, the item will be manufactured without an 'A' Rating.

| Addon-ons do not Addor | | n-ons available: |
|------------------------|-----|--|
| affect 'A' Rating. | (S) | Small = 15mm Kommerling/Aluplast and 20mm Swish |
| Specify (S) (M) or (L) | (M) | Medium = 25mm Kommerling and 35mm Aluplast/Swish |
| when required. | (L) | Large = 50mm Kommerling/Swish and 60mm Aluplast |

Order forms for all products can be downloaded from http://www.21stcenturywindows.co.uk Additional information for Bays/Bow windows and Entrance & French doors including minimum door sizes for each infill door panel can also be downloaded.

Full specifications for products and our Terms & Conditions of Sale can be found on our website.