
21ST CENTURY - TIMBERLOOK BI-FOLD ORDER				Page		of	
Customer		Goods £		Order Da	ate		
Address		VAT £		Customer Signature (By Signing this order you agree to Affordable			
	- Total £					Window Systems Ltd Terms & Conditions	
Tel No	-		<u> </u>		<u> </u>		
Email/Fax	-	Date Req. (ALSO INVOICE DATE)					
Post Code Job Reference				L			
Contact Quote Date		PRODUCTION CODE:	DELIVERY CODE:				
GLASS Tripleshield [ ] Stay Cool [ ] Unglazed [ ]		ARM EDGE  Black [ ]  White [ ]	Silver (Satin) [ ] Gold (Bright) [ ] Silver (Bright) [ ]				
White PVCu [ ] COLOUR OUTSIDE ONLY							
Rosewood on Brown [ ] Oak o	on White [ ] Fir Green on White [ ] Rosewood on White [					nite [ ]	
ALL COLOURS BOTH SIDES BELOW ARE ON	L 3	il [ ] Chartwell Green on White [ ]  Antique Pine on White [ ]					
Black [ ] Fir Green [ ] Anti Grey [ ] Chartwell Green [ ] (Irish	ey on White	on White		(Irish Oak)	ie on	wnite [ ]	
Cream [ ] Polar White Foil [ ] PLEASE NOTE: The base profile is on white							
* * *	All diagram	s are <u>OUTSIDE VIEW</u>	ONLY	*		 J_	
	Stack In	[ ] Stack Out	t [ ]	<b>~</b> []	<b>*</b> [][]	× ×	
	ltem	Qty				<u></u>	7
	Location			[]	<b>&gt;</b>	<b>→</b>	
	Width						] -
	Height			[]	<b>←</b> ≺(2		}
	Cill No	one [ ] Clip o	n Cill []				<u> </u>
( M [ ]	Trickle Vent No [ ] Yes [ ] In 42mm Knock On only, show position on diagram			[]	M	<b>&gt;</b>	<b>→</b>
	*NEW* Tilt & Lift Blinds Yes [ ] Colour						
<b>M</b> []	Notes:			[]	M	<b>}</b>	
	1101031					T	
				[]	<b>&gt;</b>	$\rightarrow$	<del>                                     </del>
[]				[]	<b>~</b> <(2)		<b>&gt;</b>
[]	will have a Le	rench Doors, Mast ver/Lever handle d e a D-Pad to inside	and the	[]	222>	<b>&gt;</b>	<del></del>
Sightlines:  132mm - Sliders/Slider 160mm - Traffic/Traffic 222mm - Slider/Traffic							





## TIMBERLOOK SLIM-SASH PVC-u BI-FOLDING DOORS

## THRESHOLD OPTIONS OPTION 1.



It is possible to recess the track 45mm into the floor

Timberlook Slim-Sash PVC-u Bi- Folding Doors have a sight line of 132mm sash to sash when doors slide to one side only.


This will double if doors are arranged to open both ways from the

centre, however it is possible to have a traffic door one way and the other doors folding in the opposite direction and the sight line will only increase by 40mm where the doors meet.

The Bi-Fold doors can open in or out and are available up to 6 metres wide in any number of configurations.

The Timberlook 60mm sash has a combination of steel, aluminium and RCM reinforcement. The RCM is welded producing a weld strength which would normally require a much wider door sash. The maximum sash width is 750mm and the minimum width is 500mm - the ideal width is 600mm to 650mm for optimal performance.

## **OPTION 2.**




By lowering the external brickwork
- the track can be installed flush
with the internal floor


- The Timberlook Bi-Fold aluminium thresher is 52mm high.
- The Threshold can be fitted flush to the inside and outside floor and is also available with an external aluminium sill that does not increase the threshold height of 52mm.
- The rollers are concealed and are resistant to attack from potential intruders
- Hardened steel hook locks, dead bolts and top/bottom shootbolts are specified for high security and flat handles minimise stacking space when opened.
- The wheels which are stainless steel operate quietly and smoothly and have sealed bearings for maintenance free use.
- There are 4 expansion seals between each door.

Guide

Rollers



Fitted in the conventional way the upstand is only 52mm while conventional PVC-u Bi-Folding doors have an upstand between 100mm and 140mm



The HEAD & THRESHER are aluminium and do not have a PVC-u frame

The Aluminium Head & Thresher encapsulate the running gear so that the door cannot be lifted from the track.